

XE150



Refrigerator-press-formed sides GN2/1-X-treme

One-piece structure in AISI 304 stainless steel. The storage chamber consists of AISI 304 stainless steel press-formed internal sides, 20 positions spaced 55cm. Single compartment, GN2/1. 2 doors. Temperature ranges: -2/+8°C. Electronic control panel. Fan-assisted refrigeration with external evaporator. High efficiency motor unit. Automatic defrosting electric type. Lighting and key-operated lock.



General information

Supplier/producer 's name	SAGI SPA
Series	X-TREME
Supplier's model identifier	XE150
Category	vertical cabinet
Type	refrigerator
Line	catering - GN 2/1

Technical features

Temperature ranges, °C	-2/+8
Energy Efficiency Class	A
Energy consumption E24, kW/h	1,52
Energy consumption/year, kW/h	555
Method for energy consumption	EN 16825
Energy Efficiency Index	24,9
Net usable volume, lt	986
Volume, gross, lt	1150
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R600a/3
Refrigerant charge, kg	0,07+0,07
LWA dB(A)	40
Cooling system	ventilated refrigeration system
Defrosting	automatic by heating elements
Evaporation of condense drain	automatic

Refrigerator-press-formed sides GN2/1-X-treme

SAGI S.p.a. con socio unico

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy

www.sagispa.it | info@sagispa.it

Sagi S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 15/05/2018 11.42.45



XE150



Refrigeration power at -10°C W	377+377
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,54

Construction features

Structure	one - piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	diamond treated bottom with drain hole
Insulation thickness, mm	75
Door	2 doors in AISI 304 stainless steel
Standard hinging door	with self-closing device for openings inferior to 90°
Door handle	integrated full-height
Internal structure	with press-formed internal sides in AISI 304 stainless steel
Positions (n.)/spaced, mm	20/55
Evaporator	positioned outside the compartment
Easymaintenance	accessibility to all the functional and control components via a retractable front panel
Safety interlock switch	yes, to stop internal fan and switch on compartment light
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	115 ÷ 165

Control and functions

Kind of control	electronic pannel control board
Display	digital
Alarms	optical and acoustical
Functions/programs	Hyper Cold, Energy Saving

Standard

Key-lock	yes
Lighting	yes
Shelves (n.)	8 AISI 304 stainless steel
Shelf's dimensions, cm	53x65 (GN 2/1)
Shelf loading capacity, kg	60

Dimensions and weights

Packaging dimension (LxDxH),cm	145x85,5x207
Exterior dimension (LxDxH), cm	139x80x204
Weight, packed, kg	210
Weight, kg	190

Refrigerator-press-formed sides GN2/1-X-treme

SAGI S.p.a. con socio unico

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy

www.sagispa.it | info@sagispa.it

Sagi S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

2/2 PRINTED 15/05/2018 11.42.45

