

ME150LT

Refrigerator-GN2/1-AISI 304-Nex-to

One-piece structure in AISI 304 stainless steel. The storage chamber consists of AISI 304 stainless steel press-formed internal sides, 20 positions spaced 55cm. Single compartment, GN2/1. 2 doors. Temperature ranges: -2/+8°C. Control panel with digital thermometer- thermostat. Ventilated refrigerating system. Automatic defrosting. Lighting and key-operated lock.



General information

Supplier/producer 's name	SAGI SPA
Series	Nex-to
Supplier's model identifier	ME150LT
Category	vertical cabinet
Type	refrigerator
Line	catering - GN 2/1

Technical features

Temperature ranges, °C	-2/+8
Energy Efficiency Class	E
Energy consumption E24, kW/h	4,53
Energy consumption/year, kW/h	1521
Method for energy consumption	EN 16825
Energy Efficiency Index	77,5
Net usable volume, lt	800
Volume, gross, lt	1150
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R134a/1430
Refrigerant charge, kg	0,28
LWA dB(A)	50
Cooling system	ventilated refrigeration system
Defrosting	automatic
Evaporation of condense drain	automatic

Refrigerator-GN2/1-AISI 304-Nex-to

SAGI S.p.a. con socio unico

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy

www.sagispa.it | info@sagispa.it

Sagi S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 09/05/2018 11.32.06



ME150LT



Refrigeration power at -10°C W	462
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,58

Construction features

Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	with rounded corners
Insulation thickness, mm	75
Door	2 doors in AISI 304 stainless steel
Door handle	integrated full-height
Internal structure	with press-formed internal sides in AISI 304 stainless steel
Positions (n.)/spaced, mm	20/55
Evaporator	with an anti-corrosion treatment
Easymaintenance	accessibility to all the functional and control components via a retractable front panel
Safety interlock switch	yes, to stop internal fan and switch on compartment light
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	115 ÷ 165

Control and functions

Kinf of control	thermometer-thermostat
Display	digital
Alarms	optical

Standard

Key-lock	yes
Lighting	yes
Shelves (n.)	6, plastic coated
Shelf's dimensions, cm	53x65 (GN 2/1)
Shelf loading capacity, kg	60

Dimensions and weights

Packaging dimension (LxDxH),cm	145x85,5x207
Exterior dimension (LxDxH), cm	139x83,5x204
Weight, packed, kg	210
Weight, kg	190

Refrigerator-GN2/1-AISI 304-Nex-to

