

CDRI



Refrigerator-1 trolley-AISI 304-Roll-In

One-piece structure in AISI 304 stainless steel. 1 door. Interior designed to take trolleys with capacity 20 GN 2/1 or EN 60x80cm containers. Temperature ranges: +2/+10°C. Electronic control panel. Fan-assisted refrigeration with external evaporator. Automatic "intelligent" defrosting. Equipped with lighting and key-operated lock.



General information

Supplier/producer 's name	SAGI SPA
Series	Class Roll In
Supplier's model identifier	CDRI
Category	vertical cabinet
Type	refrigerator
Line	catering - roll in

Technical features

Temperature ranges, °C	+2/+10
Energy Efficiency Class	product are excluded from the European energy classification label according to EU Regulation 2015/1
Net usable volume, lt	1450
Volume, gross, lt	1526
Climate class	5 (+40°C, 40% R.H.)
Refrigerant/GWP	R404A/3922
LWA dB(A)	62
Cooling system	ventilated refrigeration system
Defrosting	automatic "intelligent" defrosting by hot gas, which activates only when necessary
Evaporation of condense drain	automatic
Refrigeration power at -10°C W	566
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,8

Construction features

SAGI S.p.a. con socio unico

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy

www.sagispa.it | info@sagispa.it

Sagi S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 08/05/2018 02.24.25

Refrigerator-1 trolley-AISI 304-Roll-In



Structure	panels
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Insulation thickness, mm	70
Door	Door clearance (LxHxD) 70x181,5x88 cm
Standard hinging door	on the right/reversible on the site with self-closing device for openings inferior to 90°
Internal structure	for trolleys

Control and functions

Kinf of control	electronic pannel control board
Display	digital
Alarms	optical and acoustical
Functions/programs	Hyper Cold, Energy Saving

Standard

Key-lock	yes
Lighting	yes

Dimensions and weights

Packaging dimension (LxDxH),cm	116x119x240
Exterior dimension (LxDxH), cm	105,5x105,5x225
Weight, packed, kg	200
Weight, kg	180